

Title of Invention: High Contrast Surface  
Marking Using Irradiation of Electro-  
Statically Applied Marking Materials  
Inventor's Name: Harrison, Paul  
Serial No: 09/880,391

#4

1/9




FIG. 1



FIG. 2



09880391 092001

+

+

Title of Invention: High Contrast Surface  
Marking Using Irradiation of Electro-  
Statically Applied Marking Materials  
Inventor's Name: Harrison, Paul  
Serial No: 09/880,391

2/9



Title of Invention: High Contrast Surface  
Marking Using Irradiation of Electro-  
Statically Applied Marking Materials  
Inventor's Name: Harrison, Paul  
Serial No: 09/880,391

100250 "15000000

3/9





FIG. 5

+

1. *Staphylococcus aureus* (Staph. aureus) is a common cause of skin infections, including abscesses, boils, and impetigo. It is also a leading cause of hospital-acquired infections.



+

Title of Invention: High Contrast Surface  
Marking Using Irradiation of Electro  
Statically Applied Marking Materials  
Inventor's Name: Harrison, Paul  
Serial No: 09/880,391

5/9

<u>Substrate Materials</u>	<u>Marking Materials</u>	<u>Beam Speed</u>	<u>Power (watts)</u>	<u>Freq (Khz/Cw)</u>
Aluminum	Mixed Metal Oxide	200mm/sec	5 watts	CW
Aluminum	Glass Frit	250mm/sec	5 watts	CW
Brass	Mixed Metal Oxide	200mm/sec	5 watts	CW
Ceramic	Glass Frit	200mm/sec	5 watts	CW
China	Glass Frit	200mm/sec	5 watts	CW
Copper	Mixed Metal Oxide	100mm/sec	5 watts	20 KHz
Auto Safety Glass	Glass Frit	200mm/sec	5 watts	CW
CRT Display Glass	Glass Frit	200mm/sec	5 watts	CW
Flat Panel Display Glass	Glass Frit	200mm/sec	5 watts	CW
Microscope Slide Glass	Glass Frit	200mm/sec	5 watts	CW
Nickel	Mixed Metal Oxide	200mm/sec	5 watts	CW
Nylon™	Mixed Metal Oxides	250mm/sec	5 watts	CW
Porcelain	Glass Frit	200mm/sec	5 watts	CW
PVC	Mixed Organic Pigments	200mm/sec	5 watts	CW
Stainless Steel	Mixed Metal Oxide	200mm/sec	5 watts	CW
Stainless Steel	Glass Frit	300mm/sec	5 watts	CW
Teflon™	Mixed Metal Oxides	200mm/sec	5 watts	CW
Tin	Mixed Metal Oxide	200mm/sec	5 watts	CW
Titanium	Mixed Metal Oxide	200mm/sec	5 watts	CW

FIG. 8

Title of Invention: High Contrast Surface  
 Marking Using Irradiation of Electro  
 Statically Applied Marking Materials  
 Inventor's Name: Harrison, Paul  
 Serial No: 09/880,391

5/9

<u>Substrate Materials</u>	<u>Marking Materials</u>	<u>Beam Speed</u>	<u>Power (watts)</u>	<u>Freq (Khz/Cw)</u>
Aluminum	Mixed Metal Oxide	200mm/sec	5 watts	CW
Aluminum	Glass Frit	250mm/sec	5 watts	CW
Brass	Mixed Metal Oxide	200mm/sec	5 watts	CW
Ceramic	Glass Frit	200mm/sec	5 watts	CW
China	Glass Frit	200mm/sec	5 watts	CW
Copper	Mixed Metal Oxide	100mm/sec	5 watts	20 KHz
Auto Safety Glass	Glass Frit	200mm/sec	5 watts	CW
CRT Display Glass	Glass Frit	200mm/sec	5 watts	CW
Flat Panel Display Glass	Glass Frit	200mm/sec	5 watts	CW
Microscope Slide Glass	Glass Frit	200mm/sec	5 watts	CW
Nickel	Mixed Metal Oxide	200mm/sec	5 watts	CW
Nylon™	Mixed Metal Oxides	250mm/sec	5 watts	CW
Porcelain	Glass Frit	200mm/sec	5 watts	CW
PVC	Mixed Organic Pigments	200mm/sec	5 watts	CW
Stainless Steel	Mixed Metal Oxide	200mm/sec	5 watts	CW
Stainless Steel	Glass Frit	300mm/sec	5 watts	CW
Teflon™	Mixed Metal Oxides	200mm/sec	5 watts	CW
Tin	Mixed Metal Oxide	200mm/sec	5 watts	CW
Titanium	Mixed Metal Oxide	200mm/sec	5 watts	CW

FIG. 8




FIG. 9

7/9




FIG. 10 a

GLASS SLIDE - PORCELAIN/GLASS FRIT





FIG. 10 b



T00260" T6E00860

8/9

X-PROFILE/2 PT/RADIAL



Rq: 2.92 um  
Ra: 1.97 um  
Rt: 14.09 um  
Rp: 13.17 um  
Rv: -0.92um


L: 0.05 mm -0.83 um  
R: 0.33 mm 2.23 um  
D: 0.27 mm 3.05 um  
Angle: 0.64°  
Curve: -14.65 mm  
Terms: None  
AvgHt: 0.61 um  
Area 0.17 um<sup>2</sup>

FIG. 10c

100260" 16C08860

9/9

Y-PROFILE/CIRCULAR



Rq: 2.85 um  
Ra: 2.44 um  
Rt: 9.96 um  
Rp: 7.79 um  
Rv: -2.16 um

L: 13.93 um    Angle: 0.98°  
R: 170.62 um    Curve: -492.76 um  
D: 156.69 um    Terms: None  
AvgHt: 1.20 um  
Area: 187.84 um<sup>2</sup>

FIG. 10 d